

訂購代碼 Ordering Code

圖形符號 Symbol

PU - 220 - 01 - AC110V - E



- 規格代碼**
PU 二口二位電磁閥
Specification
PU 2/2 Way
- 動作方式**
220: 直動式
Operation
220: Direct
- 接管口徑**
Port Size
01: 1/8"
02: 1/4"
03: 3/8"
04: 1/2"
06: 3/4"
08: 1"
- 標準電壓**
Standard Voltage
DC12V
DC24V
AC24V 50Hz/60Hz
AC110V 50Hz/60Hz
AC220V 50Hz/60Hz
AC380V 50Hz/60Hz
- 油封代號**
空白: NBR
E: EPDM(蒸汽用)
V: VITON
(高溫、瓦斯及真空用)
Sealing
Blank: NBR
E: EPDM for steam
V: VITON (for high temperature, gas, vacuum)

規格 Specification

型號 Model	PU220-01	PU220-02	PU220-03	PU220-04	PU220-06	PU220-08
工作介質 Working Medium	空氣、水、油 Air, Water, Oil					
動作方式 Operation	直動式 Direct					
型式 Type	常閉型 Normal Close					
流量孔徑 Orifice	1.5mm	2.3mm	8.0mm	13mm	20mm	25mm
CV 值 CV Value	0.10	0.18	1.00	4.00	8.60	11.00
接管口徑 Port Size	1/8"	1/4"	3/8"	1/2"	3/4"	1"
使用介質粘滯度 Operation Fluid Viscosity	50 CST 以下 Below					
使用壓力 Working-pressure	0 ~ 0.7MPa					
最大耐壓力 Max. Test Pressure	1.05MPa					
工作溫度 Max. Ambient Temperature	-5 ~ 80°C					

外觀尺寸 Overall Dimension

尺寸表 Dimension



型號 Model	口徑 Bore	A	B	C
PU220-01	1/8	22	72	22
PU220-02	1/4	35	75.5	25.4
PU220-03	3/8	55	79.5	30
PU220-04	1/2	66.5	101	48
PU220-06	3/4	71	107	48
PU220-08	1	96	120	70